## Safety Rail Height – 3 Models

**LOW** – This is our classic *SleepSafe*® bed with safety rails ranging up to 17¼" above the mattress depending on the foundation choice.

**MEDIUM** – The *SleepSafe® II* provides protection ranging up to 27" above the mattress depending on the foundation choice.

**TALL** – The *SleepSafer*® provides protection up to 36¼" above the mattress depending on the foundation choice. The *SleepSafer*® *Extension Kit* offers an <u>additional 16¾" of safety rail height</u> when ordered or retrofitted to your existing SleepSafer® Bed.



SleepSafe®	SleepSafe® II	SleepSafer®

		sieepsate" siee	psare" ii sieepsarer"
SleepSafe® Bed <b>Specifications</b>	Low Bed SleepSafe®	Medium Bed SleepSafe® II	Tall Bed / Extension SleepSafer®
SAFETY RAIL HEIGHT Distance from the top of mattress to	the top of the safety rail	<u>-</u>	
Fixed Foundation with Box Spring (Choice of settings)	12" or 8¾"	21¾" or 16½"	31" or 24¾" / 47¾" or 41½"
Fixed Foundation with Bunkie Board (Choice of settings)	17¼" or 14"	27" or 21¾"	36¼" or 30" / 53" or 46¾"
Manual Articulating Foundation	15" or 11¾"	24¾" or 19½"	34" or 27¾" / 50¾ or 44½"
Manual HI-LO Foundation	LO 11½" to EVEN with rail	LO 21¼" to HI 9½" or LO 16" to HI 4¼"	LO 30½" to HI 18¾" / LO 47¾" to HI 35½
Articulating Foundation (Choice of settings)	15" or 11¾"	24¾" or 19½"	34" or 27¾" / 50¾ or 44½"
Electric HI-LO Foundation (LO to HI Settings)	LO 111/2" to HI 11/4" below rail	LO 211/4" to HI 11" or LO 16" to HI 53/4"	LO 30" to HI 20¼" / LO 46¾ to HI 37"
MATTRESS HEIGHT Distance from the top of the mattress to	the floor.		
Fixed Foundation with Box Spring (Choice of settings)	22¾" or 26"	23" or 281/4"	22¾" or 29"
Fixed Foundation with Bunkie Board (Choice of settings)	17½" or 20¾"	17¾" or 23"	17½" or 23¾"
Manual Articulating Foundation	19¾" or 23"	20" or 25¼"	19¾" or 26"
Manual HI-LO Foundation	LO 231/4" to HI 35"	LO 23½" to HI 35¼" or LO 28¾" to HI 40½"	LO 23¼" to HI 35"
Articulated Foundation (Choice of settings)	19¾" or 23"	20" or 25¼"	19¾" or 26"
Electric HI-LO Foundation - (LO to HI Settings)	LO 231/4" to HI 331/2"	LO 23½" to HI 33¾" or LO 28¾" to HI 39"	LO 23¼" to HI 33½"
FLOOR TO RAIL HEIGHT	34¾"	44¾"	53¾" / 71"
Distance from the top of the rail to the floor.			
OVERALL OUTSIDE DIMENSIONS			
Twin	42¼″W x 80½″L x 43″H	42¼″W x 80½″L x 53″H	42¼"W x 80¼"L x 56"H (72¼"H w/Ext.)
Full	56"W x 80"L x 43"H	56"W x 80"L x 53"H	56"W x 80"L x 56"H (72¼"H w/Ext.)
Queen	65"W x 80"L x 43"H	65"W x 80"L x 53"H	65"W x 80"L x 56"H (72¼"H w/Ext.)
MATTRESS SIZE			
Twin	38"W x 77"L	38"W x 77"L	38"W x 77"L
Full	51"W x 77"L	51"W x 77"L	51"W x 77"L
Queen	60″W x 77″L	60"W x 77"L	60"W x 77"L
UNDER BED FLOOR CLEARANCE			
Standard Models	7"	7"	6¾"
<b>TRANSFER HEIGHT</b> Distance from the top edge of the folded down safety rail to the floor.	21¼" with Safety Rail On 19¾" with Safety Rail Off	31" with Safety Rail On 29½" with Safety Rail Off	25" with Safety Rail On 23½" with Safety Rail Off
		1	1







